



10/049507  
JC10 Rec'd PCT/PTO 13 FEB 2002

Total claims	10	-	20	=		x	\$18.00	=	\$0.00
Independent claims	<u>5</u>	-	3	=	<u>2</u>	x	\$84.00	=	<u>\$168.00</u>
Base Fee									\$890.00
<b>TOTAL FILING FEE</b>									<u>\$1058.00</u>
<b>Recordation of Assignment</b>									<u>\$ 40.00</u>
<b>TOTAL FEE</b>									<u>\$1098.00</u>



Sughrue

SUGHRUE MION, PLLC


Commissioner for Patents  
Washington, D.C. 20231  
Box PCT  
Attorney Docket Q68452  
Page 2  
February 13, 2002

Checks for the statutory filing fee of \$1058.00 and Assignment recordation fee of \$40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from:

<u>Country</u>	<u>Application No</u>	<u>Filing Date</u>
Germany	00440174.1	June 14, 2000

Respectfully submitted,

  
David J. Cushing  
Registration No. 28,703

SUGHRUE MION, PLLC  
2100 Pennsylvania Avenue, N.W.  
Washington, D.C. 20037-3213  
Telephone: (202) 293-7060  
Facsimile: (202) 293-7860

Date: February 13, 2002

10049507-021302

**PATENT APPLICATION**

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re application of

PCT/EP01/06254

PETERS, MARCO ET AL., et al.

Attorney Docket Q68452

Appln. No.: Not Assigned

Confirmation No.: Not Assigned

Group Art Unit: Not Assigned

Filed: February 13, 2002

Examiner: Not Assigned

For: TELECOMMUNICATION SYSTEM, AND NETWORK, AND TERMINAL, AND  
GENERATOR, AND METHOD

**PRELIMINARY AMENDMENT**

Commissioner for Patents  
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

**IN THE SPECIFICATION:**

Please amend the specification as shown in the accompanying marked-up copy of the  
specification.

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[illegible]

Table 1. Continued	
Age	0.000000
Age <sup>2</sup>	0.000000
Age <sup>3</sup>	0.000000
Age <sup>4</sup>	0.000000
Age <sup>5</sup>	0.000000
Age <sup>6</sup>	0.000000
Age <sup>7</sup>	0.000000
Age <sup>8</sup>	0.000000
Age <sup>9</sup>	0.000000
Age <sup>10</sup>	0.000000
Age <sup>11</sup>	0.000000
Age <sup>12</sup>	0.000000
Age <sup>13</sup>	0.000000
Age <sup>14</sup>	0.000000
Age <sup>15</sup>	0.000000
Age <sup>16</sup>	0.000000
Age <sup>17</sup>	0.000000
Age <sup>18</sup>	0.000000
Age <sup>19</sup>	0.000000
Age <sup>20</sup>	0.000000
Age <sup>21</sup>	0.000000
Age <sup>22</sup>	0.000000
Age <sup>23</sup>	0.000000
Age <sup>24</sup>	0.000000
Age <sup>25</sup>	0.000000
Age <sup>26</sup>	0.000000
Age <sup>27</sup>	0.000000
Age <sup>28</sup>	0.000000
Age <sup>29</sup>	0.000000
Age <sup>30</sup>	0.000000
Age <sup>31</sup>	0.000000
Age <sup>32</sup>	0.000000
Age <sup>33</sup>	0.000000
Age <sup>34</sup>	0.000000
Age <sup>35</sup>	0.000000
Age <sup>36</sup>	0.000000
Age <sup>37</sup>	0.000000
Age <sup>38</sup>	0.000000
Age <sup>39</sup>	0.000000
Age <sup>40</sup>	0.000000
Age <sup>41</sup>	0.000000
Age <sup>42</sup>	0.000000
Age <sup>43</sup>	0.000000
Age <sup>44</sup>	0.000000
Age <sup>45</sup>	0.000000
Age <sup>46</sup>	0.000000
Age <sup>47</sup>	0.000000
Age <sup>48</sup>	0.000000
Age <sup>49</sup>	0.000000
Age <sup>50</sup>	0.000000
Age <sup>51</sup>	0.000000
Age <sup>52</sup>	0.000000
Age <sup>53</sup>	0.000000
Age <sup>54</sup>	0.000000
Age <sup>55</sup>	0.000000
Age <sup>56</sup>	0.000000
Age <sup>57</sup>	0.000000
Age <sup>58</sup>	0.000000
Age <sup>59</sup>	0.000000
Age <sup>60</sup>	0.000000
Age <sup>61</sup>	0.000000
Age <sup>62</sup>	0.000000
Age <sup>63</sup>	0.000000
Age <sup>64</sup>	0.000000
Age <sup>65</sup>	0.000000
Age <sup>66</sup>	0.000000
Age <sup>67</sup>	0.000000
Age <sup>68</sup>	0.000000
Age <sup>69</sup>	0.000000
Age <sup>70</sup>	0.000000
Age <sup>71</sup>	0.000000
Age <sup>72</sup>	0.000000
Age <sup>73</sup>	0.000000
Age <sup>74</sup>	0.000000
Age <sup>75</sup>	0.000000
Age <sup>76</sup>	0.000000
Age <sup>77</sup>	0.000000
Age <sup>78</sup>	0.000000
Age <sup>79</sup>	0.000000
Age <sup>80</sup>	0.000000
Age <sup>81</sup>	0.000000
Age <sup>82</sup>	0.000000
Age <sup>83</sup>	0.000000
Age <sup>84</sup>	0.000000
Age <sup>85</sup>	0.000000
Age <sup>86</sup>	0.000000
Age <sup>87</sup>	0.000000
Age <sup>88</sup>	0.000000
Age <sup>89</sup>	0.000000
Age <sup>90</sup>	0.000000
Age <sup>91</sup>	0.000000
Age <sup>92</sup>	0.000000
Age <sup>93</sup>	0.000000
Age <sup>94</sup>	0.000000
Age <sup>95</sup>	0.000000
Age <sup>96</sup>	0.000000
Age <sup>97</sup>	0.000000
Age <sup>98</sup>	0.000000
Age <sup>99</sup>	0.000000
Age <sup>100</sup>	0.000000

[illegible]

Preliminary Amendment  
Attorney Docket Q68452

**APPENDIX**

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

**IN THE SPECIFICATION:**

See the attached marked-up version of the application for the Examiner's review.

2025-01-20 10:54:00

10/049507

JC13 Rec'd PCT/PTO 13 FEB 2002

## SUBSTITUTE SPECIFICATION

10/049507

**Description****TELECOMMUNICATION SYSTEM, AND NETWORK, AND TERMINAL,  
AND GENERATOR, AND METHOD****BACKGROUND OF THE INVENTION:**

The invention is based on a priority application PCT/EP 01/06254 which is hereby incorporated by reference.

The invention relates to a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

Such a telecommunication system is known in general, with said terminal for example being a fixed analog or digital terminal comprising an analog or digital modem (such a combination for example being an analog or digital screenphone or a pc) or being a mobile (for example GSM or UMTS) or a cordless (for example DECT) terminal, with each one of said terminals nowadays usually being provided with a browser, and with said control signal for example being a (part of a) Uniform Resource Locator or URL (and/or with said control signal being converted into said (part of a) URL) to be entered by said user for example through text via a terminal's keyboard or through a mouse click via a terminal's mouse or through a touch via a terminal's touch screen or through voice/speech via a terminal's microphone. At least a part of said network corresponds with at least a part of an INTERNET and/or INTRANET, and comprises said memory (for example a server) in which said information is stored at said at least one memory location defined by said at least one address signal (which address signal for example corresponds with an IP address or for example is generated in response to said IP address), which information is to be supplied

to said terminal in response to said control signal. Thereto, a Domain Name Server or DNS (usually located in said network) is used to convert said (part of a) URL into said IP address, which IP address is sent back to said (browser in said) terminal. In response to the receipt of this IP address, said browser establishes for example a TCP (Transmission Control Protocol) or a UDP (User Datagram Protocol) connection with for example a (part of a) server as defined by said IP address for receiving said information.

Such a telecommunication system is disadvantageous, inter alia, due to being user-friendly insufficiently.

It is an object of the invention, inter alia, to provide a telecommunication system as described in the preamble, which is more user-friendly.

#### SUMMARY OF THE INVENTION:

Thereto, the telecommunication system according to the invention comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

By introducing said generator for generating in a user-dependent way, the telecommunication system has been individualized. As a consequence, a first user entering a specific control signal will receive first information stored in a first memory and read out from this first memory in response to a first address signal, and a second user entering the same specific control signal will receive second information (different from said first information) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example a user identification (comprising for example the terminal's IP address and/or a number of a so-called source port) being involved in a conversion of said (part of a) URL into said IP address.



The invention is based on the insight, inter alia, that an individualized telecommunication system based upon at least one user-dependency is more user-friendly.

The invention solves the problem, inter alia, of providing a telecommunication system which is more user-friendly.

A first embodiment of the telecommunication system according to the invention is that said user-dependent way comprises at least one location-dependency and/or at least one time-dependency.

By introducing said location-dependency, a first user being in/near Brussels and entering a specific control signal (for example a mouse click on an icon for receiving the weather forecast) will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and a second user being in/near Paris and entering the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example said first user being in/near Brussels and said second user being in/near Paris.

Said time-dependency for example allows said first user after having entered a specific control signal (for example a mouse click on an icon for receiving the weather forecast) to receive first information from Monday till Friday (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and allows said first user after having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) to receive second information during the

weekend (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example said first user working in Brussels and living in Antwerp.

A second embodiment of the telecommunication system according to the invention is that said at least one part of said generator is located in said network.

By locating said generator (substantially) in the network, the terminal just needs minimal adaptations or does not even need to be adapted at all.

According to a first option, said generator corresponds with one or more Domain Name Servers or DNSs, with said location-dependencies being realized by storing in different DNSs different IP addresses but all to be read out in response to the same specific control signal. So, said first user being in/near Brussels and having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS in/near Brussels and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and a second user being in/near Paris and having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get a second IP address from a DNS in/near Paris and receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that at least parts of said DNS and generator are integrated.

According to a second option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said second option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

According to a third option, said generator corresponds with one or more DNSs, with said time-dependencies being realized by using clock signals for reading out from a DNS a first IP address in response to said specific control signal in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said specific control signal in case of said clock signal having a second value. So, said first user having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address from Monday till Friday, and said first user

having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get a second IP address from a DNS and receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address) during the weekend, due to for example said first user working in Brussels and living in Antwerp. Said third option is very advantageous in that at least parts of said DNS and generator are integrated.

According to a fourth option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in Antwerp. Said fourth option is very advantageous in that the DNS does not need to be adapted.

A third embodiment of the system according to the invention is that said at least one part of said generator performs said generating in dependence of a location signal to be generated via said network.

By providing said generator with said location signal originating from said Point-of-Presence or PoP (the telephone number of this PoP) or originating via said PoP (the user's telephone number or a user identification or the user's IP address), said generators (said DNSs in case of said first option as well as said converters in case of said second option) can be designed more generally and do not need to be adapted per location, due to said location signals taking care of the individualization.

A fourth embodiment of the system according the invention is that at least one part of said generator is located in said terminal.

By locating said generator (substantially) in the terminal, the network just needs minimal adaptations or does not even need to be adapted at all.

According to a first option, said generator performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Thereto, said terminal for example receives location information from the network (in case of said terminal being a mobile terminal, base station controller or BSC information could be used, and in case of said terminal being a fixed or mobile terminal, PoP information could be used). Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said

second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

According to a second option, said generator performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in Antwerp. Said second option is very advantageous in that the DNS does not need to be adapted.

10049507-021302

A fifth embodiment of the system according the invention is that said at least one part of said generator performs said generating in dependence of a further location signal to be generated via said terminal.

By providing said generator with said further location signal to be generated via said terminal, location-dependencies are introduced which are network-independently. For example, said further location signal originates from a Global Positioning System receiver or GPS receiver forming part of said terminal, or said further location signal is entered by said user, for example an area code. Then, in said terminal, in dependence of said further location signal, a specific control signal is converted into a location-dependent control signal, etc.

The invention further relates to a network for use in a telecommunication system for receiving at least one control signal from a user via terminal and comprising said terminal and said network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The network according to the invention comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the network according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the network is involved.

The invention yet further relates to a terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to

said terminal and stored at at least one memory location defined by at least one address signal.

The terminal according to the invention comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the terminal according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the terminal is involved.

The invention also relates to a generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The generator according to the invention generates at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the generator according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the generator is involved.

The invention yet also relates to a method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.



The method according to the invention is comprises the step of generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the method according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the method is involved.

US 6,055,542 discloses a system for displaying the content of a web page based on a user's interests, US 6,029,135 discloses a hypertext navigation system controlled by spoken words, US 5,764,639 as well as US 5,889,845 disclose a system for providing a remote user with a virtual presence to an office, US 6,052,725 discloses a non-local dynamic internet protocol addressing system, US 5,898,780 discloses an apparatus for authorizing remote internet access, and US 5,598,536 discloses an apparatus for providing remote users with the same unique IP address upon each network access. Neither one of these documents discloses the telecommunication system according to the invention. All references including further references cited with respect to and/or inside said references are considered to be incorporated in this patent application.

#### BRIEF DESCRIPTION OF THE DRAWING:

The invention will be further explained at the hand of an embodiment described with respect to a drawing, whereby

#### DETAILED DESCRIPTION OF THE INVENTION

Figure 1 discloses a telecommunication system according to the invention comprising a network according to the invention and a terminal according to the invention and a generator according to the invention.

The telecommunication system according to the invention as shown in figure 1 comprises a first, fixed terminal 1 according to the invention and a second, mobile (for example GSM or UMTS) terminal 2 according to the invention and a third, fixed terminal 6 according to the invention and a fourth, cordless (for example DECT) terminal 7 according to the invention and a network 3,4,5,90,91,92,93,94 according to the invention comprising a first switch 3, a second switch 4, a third switch 5, a Base Station Controller or BSC 90 (for example GSM or UMTS), a Base Station or BS 91 (for example GSM or UMTS), a Base Station or BS 92 (for example DECT), a generator 93 according to the invention and a memory 94.

Terminal 1 (or 6) comprises a processor system 10 coupled via a control connection to man-machine-interface or MMI 11 (like a keyboard - display - microphone - loudspeaker - mouse - touchscreen etc.) and coupled via a bus 17 to transceiver 16 (comprising a modem function). Via said bus 17 as well as via control connections, processor system 10 is further coupled to receiving unit 13 and to transmitting unit 15. Via a bus 18, transceiver 16 is coupled to receiving unit 13 and to MMI 11. Via a bus 19, transceiver 16 is coupled to transmitting unit 15 and to MMI 11. Processor system 10 is coupled to (and/or even comprises) a generator 12 and a memory 14, which both are coupled to MMI 11 via control connections.

Terminal 2 (or 7) comprises a processor system 20 coupled via a control connection to man-machine-interface or MMI 21 (like a keyboard - display - microphone - loudspeaker - mouse - touchscreen etc.) and coupled via a bus 27 to transceiver 26 (comprising a modem function). Via said bus 27 as well as via control connections, processor system 20 is further coupled to receiving unit 23 and to transmitting unit 25. Via a bus 28, transceiver 26 is coupled to receiving unit 23 and to MMI 21. Via a bus 29, transceiver 26 is coupled to transmitting unit 25 and to MMI 21. Processor system 20 is coupled to (and/or even

comprises) a generator 22 and a memory 24, which both are coupled to MMI 21 via control connections. Transceiver 26 is connected to an antennae.

Switch 3 (or 5) comprises a processor system 30 coupled via a control connection to a coupling unit 31. Processor system 30 is coupled to (and/or even comprises) a generator 32 and a memory 34, which both are coupled to coupling unit 31 via control connections. Coupling unit 31 is further coupled to via control connections to a receiving unit 35 and a transmitting unit 36 and a processing unit 33.

Switch 4 (or 5) comprises a processor system 40 coupled via a control connection to a coupling unit 41. Processor system 40 is coupled to (and/or even comprises) a generator 42 and a memory 44, which both are coupled to coupling unit 41 via control connections. Coupling unit 41 is further coupled to via control connections to a receiving unit 45 and a transmitting unit 46 and a processing unit 43.

Transceiver 16 of terminal 1 is coupled via a connection 80 to coupling unit 31 of switch 3, which coupling unit 31 is further coupled via a connection 83 to coupling unit 41 of switch 4 and via a connection 81 to BSC 90, which is coupled via a connection 82 to BS 91 for mobile communication with terminal 2. Coupling unit 41 of switch 4 is further coupled via a connection 87 to generator 93 and via a connection 88 to memory 94 and via a connection 84 to switch 5, which via a connection 85 is coupled to terminal 6 and via a connection 86 is coupled to BS 92 for cordless communication with terminal 7.

The telecommunication system according to the invention as shown in figure 1 functions as follows.

According to a first embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the

INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 2 via connection 81 and BSC 90 and connection 82 and BS 91. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he

enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 7 via connection 86 and BS 92. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said first embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said first embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a second embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 under control of processor system 30. Generator 32 converts said URL into a first converted URL, which via coupling unit 31 and connection 83 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being

for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 under control of processor system 50. Generator 52 converts said URL into a second converted URL, which via coupling unit 51 and connection 84 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said second embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being

designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said second embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a third embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 4 via BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83. In switch 4, said URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said URL into a first IP address (thereby using the fact that said URL has arrived via connection 83 and switch 3 in/near Brussels), which via coupling unit 41 under control of processor system 40 is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.



The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 4 via BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84. In switch 4, said same URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said same URL into a second IP address (different from said first IP address, thereby using the fact that said URL has arrived via connection 84 and switch 5 in/near Paris), which via coupling unit 41 under control of processor system 40 is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way, thereby using location signals generated via said network.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said third embodiment, other location signals generated via said network are used, for example in case of terminal 2 being involved, location signals indicating that said URL has arrived via BS 91 and/or connection 82 and/or BSC 90 and/or connection 81 are supplied via connection 83 and coupling unit 41 to generator 42, and in case of terminal 7 being involved, location signals indicating that said URL has arrived via BS 92 and/or connection 86 are supplied via connection 84 and coupling unit 41 to generator 42. Or yet other location signals generated via said network are used, for example a telephone number of terminal 2 and/or 7, and/or an IP address of terminal 2 and/or 7, and/or a user identification number, in which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 44, for example.

According to a second alternative to said third embodiment, further location signals generated via said terminal are used, for example in case of terminal 2 being involved, said terminal 2 could be provided with a Global Positioning System receiver or GPS receiver, whereby GPS information is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or said user enters an area code via MMI 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, and in case of terminal 7 being involved, said user could enter an area code via MMI 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

According to a third alternative to said third embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a fourth alternative to said third embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a fourth embodiment, for example generator 93 is a Domain Name Server or DNS, and generators 22 and 72 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) generating a Uniform Resource Locator or URL, which is supplied to generator 22 for converting said URL into a first converted URL (thereby in general generator 22 will use said location signals and/or said other location signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in

memory 24). Via transmitting unit 25 and/or transceiver 26, said first converted URL is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) generating the same Uniform Resource Locator or URL, which is supplied to generator 72 for converting said URL into a second converted URL (thereby in general generator 72 will use said location signals and/or said other location signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in memory 74). Via transmitting unit 75 and/or transceiver 76, said second converted URL is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via

transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said fourth embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said fourth embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a fifth embodiment, a user using terminal 1 and being in/near Brussels has been connected to the INTERNET or an INTRANET via his terminal 1 and connection 80 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via MMI 11

for receiving the local weather forecast) which results in his browser (running in processor system 10) sending a Uniform Resource Locator or URL via transmitting unit 15 and/or transceiver 16 to switch 3 via connection 80. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 1 via connection 80. In terminal 1, said first IP address is received via transceiver 16 and/or receiving unit 13 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 6. At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 6 and connection 85 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via MMI 61 for receiving the local weather forecast) which results in his browser (running in processor system 60) sending the same Uniform Resource Locator or URL via transmitting unit 65 and/or transceiver 66 to switch 5 via connection 85. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 6 via connection 85. In terminal 6, said

"004050" 004050

second IP address is received via transceiver 66 and/or receiving unit 63 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said fifth embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, etc. Or generators 12 and 62 are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

According to a second alternative to said fifth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of terminal 1 and/or 6, and/or an IP address of terminal 1 and/or 6, and/or a user identification number (for example to be entered via MMI 11 or 61 in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), in which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

According to a third alternative to said fifth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via MMI 11 or 61, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

According to a sixth embodiment, for example in addition to the location-dependencies described before, or completely separated from these location-dependencies described before, time-dependencies are introduced. Generator 93 corresponds with a DNS, with said time-dependencies being realised by using clock signals for reading out from said DNS a first IP address in response to said URL in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said URL in case of said clock signal having a second value. So, said user having entered said URL sometime from Monday till Friday (for example a mouse click on an icon for receiving the weather forecast) will get said first IP address from said DNS and receive first information (weather forecast for Brussels) stored in said memory and read out from this memory in response to said first IP address, and said user having entered the same URL during the weekend (for example a mouse click on the same icon for receiving the weather forecast) will get said second IP address from said DNS and receive second information (weather forecast for Antwerp) stored in said memory and read out from said memory in response to said second IP address (different from said first IP address), due to for example said user working in Brussels and living in Antwerp.

According to a first alternative to said sixth embodiment, generator 93 is a DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, with said DNS reading out a first IP address in response to said first converted URL and reading out a



second IP address in response to said second converted URL etc. Said time-dependencies could again be realized by using clock signals for reading out from said generators a first converted URL in response to said URL in case of a clock signal having a first value and for reading out from said generators a second converted URL in response to said URL in case of said clock signal having a second value. Or generators 12 and 62 are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

According to a second alternative to said sixth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of a terminal, and/or an IP address of a terminal, and/or a user identification number (for example to be entered via an MMI in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), whereby said user for example could have informed said network before at which location he will be and/or what he would like to get/do etc.. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

According to a third alternative to said sixth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via an MMI, which is supplied to a switch and for example stored in a memory in said switch, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

It should be noted that said location-dependency and said time-dependency are both just examples of user-dependencies, whereby the term "user-dependencies" is to be regarded to comprise any dependency related to a user, which is not limited to direct dependencies, but does also include indirect dependencies (like a first generator at a first location generating differently from a second generator at a second location), and may include user groups and user behavior. Such dependencies can be adjusted by a user, and/or (pre)programmed, and/or dynamically adapted by the system in response to experiences from the past.

The example of the weather forecast is just an example of a kind of information and does not exclude other kinds of information, like for example flight/train schedules, traffic jam overview, yellow pages, etc.. In general any kind of information in which a user is interested could be supplied to said user, whereby the invention defines, inter alia, how said user's behavior adapts the part of said (kind of) information to be supplied to him.

All embodiments are just embodiments and do not exclude other embodiments not shown and/or described. All alternatives are just alternatives and do not exclude other alternatives not shown and/or described. Each (part of an) embodiment and/or each (part of an) alternative can be combined with any other (part of an) embodiment and/or any other (part of an) alternative. Terms like "in response to A" and "in dependence of B" do not exclude that there could be a further "in response to C" and a further "in dependence of D" etc.

Each generator will generally comprise a memory (like for example a server) which is addressed in response to user-dependencies, whereby said user-dependent addressing could take place inside said generator as well as outside said generator. Thereto an addresser could be used, which (like a hardware converter) converts an incoming address signal into an outgoing address signal for said memory, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. If not forming part of said generator, said

addressor could for part of for example a switch. Such a generator could correspond with a DNS (or include a DNS or form part of a DNS).

Each generator may alternatively be realized by a hardware converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. And/or said generator may be realized by a software converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. Therefore, said generator could be a computer program product for generating at least one address information-unit in response to at least one control information-unit in a user-dependent way (and for example running in one of said processor systems), and/or could (at least partly) be integrated with a browser, etc.

For each one of said terminals and/or said switches, alternative hardware structures are available, like an integration of two or more separated parts into one new part, or the dividing of one part into at least two separated parts, or the placing of three or more parallel parts serially, or the placing of three or more serial parts parallelly, etc.

## Claims

1. **Telecommunication system** for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at least one memory location defined by at least one address signal, said telecommunication system comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.
2. **Telecommunication system** according to claim 1, said user-dependent way comprising at least one location-dependency and/or at least one time-dependency.
3. **Telecommunication system** according to claim 1, at least one part of said generator being located in said network.
4. **Telecommunication system** according to claim 3, said at least one part of said generator performing said generating in dependence of a location signal to be generated via said network.
5. **Telecommunication system** according to claim 1, at least one part of said generator being located in said terminal.
6. **Telecommunication system** according to claim 3, at least one part of said generator performing said generating in dependence of a further location signal to be generated via said terminal.
7. **Network** for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and said network for in response to said at least one control signal addressing a

memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said network comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

8. **Terminal** for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said terminal comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.
9. **Generator** for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said telecommunication system comprising said generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.
10. **Method** for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said method comprising the step of generating at least one address signal in response to said at least one control signal in a user-dependent way.

**Abstract**

Known telecommunication systems comprising an internet terminal and a network for providing internet access/service offer a limited number of user-possibilities, which can be increased by introducing user-dependencies into the conversion of a (part of a) Uniform Resource Locator or URL into an IP address. This IP address defines the information to be supplied to said terminal, now user-dependently, for example location-dependently and/or time-dependently. Thereto, location information (Domain Name Server or DNS with location dependent content, Point-of-Presence or PoP information, terminal's IP address, terminal's phone number, user-identification, Global Positioning System or GPS information, base station controller or BSC information, area codes entered by said user) originating from said network or from said terminal and/or timing information usually originating from said network are used.

1004950 " 0312001

10/049507

JC12 Rec'd PCT/PTO 13 FEB 2002

**MARKED UP COPY COMPARING  
SUBSTITUTE SPECIFICATION TO PCT  
APPLICATION AS FILED**

10049507-033

## Description

### TELECOMMUNICATION SYSTEM, AND NETWORK, AND TERMINAL, AND GENERATOR, AND METHOD

#### BACKGROUND OF THE INVENTION:

The invention is based on a priority application PCT/EP 01/06254 which is hereby incorporated by reference.

—The invention relates to a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

——Such a telecommunication system is known in general, with said terminal for example being a fixed analog or digital terminal comprising an analog or digital modem (such a combination for example being an analog or digital screenphone or a pc) or being a mobile (for example GSM or UMTS) or a cordless (for example DECT) terminal, with each one of said terminals nowadays usually being provided with a browser, and with said control signal for example being a (part of a) Uniform Resource



Locator or URL (and/or with said control signal being converted into said (part of a) URL) to be entered by said user for example through text via a terminal's keyboard or through a mouse click via a terminal's mouse or through a touch via a terminal's touch screen or through voice/speech via a terminal's microphone. At least a part of said network corresponds with at least a part of an INTERNET and/or INTRANET, and comprises said memory (for example a server) in which said information is stored at said at least one memory location defined by said at least one address signal (which address signal for example corresponds with an IP address or for example is generated in response to said IP address), which information is to be supplied to said terminal in response to said control signal. Thereto, a Domain Name Server or DNS (usually located in said network) is used to convert said (part of a) URL into said IP address, which IP address is sent back to said (browser in said) terminal. In response to the receipt of this IP address, said browser establishes for example a TCP (Transmission Control Protocol) or a UDP (User Datagram Protocol) connection with for example a (part of a) server as defined by said IP address for receiving said information.

—Such a telecommunication system is disadvantageous, inter alia, due to being user-friendly insufficiently.

—It is an object of the invention, inter alia, to provide a telecommunication system as described in the preamble, which is more user-friendly.

#### SUMMARY OF THE INVENTION:

—Thereto, the telecommunication system according to the invention is characterised in that said telecommunication system comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

—By introducing said generator for generating in a user-dependent way, the telecommunication system has been individualised-individualized. As a consequence, a first user entering a specific control signal will receive first information stored in a first memory and read out from this first memory in response to a first address signal, and a second user entering the same specific control signal will receive second information (different from said first information) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example a user identification (comprising for example the terminal's IP address and/or a

number of a so-called source port) being involved in a conversion of said (part of a) URL into said IP address.

—The invention is based on the insight, inter alia, that an ~~individualised~~individualized telecommunication system based upon at least one user-dependency is more user-friendly.

—The invention solves the problem, inter alia, of providing a telecommunication system which is more user-friendly.

—A first embodiment of the telecommunication system according to the invention is ~~characterised in~~ that said user-dependent way comprises at least one location-dependency and/or at least one time-dependency.

—By introducing said location-dependency, a first user being in/near Brussels and entering a specific control signal (for example a mouse click on an icon for receiving the weather forecast) will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and a second user being in/near Paris and entering the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said

first or second memory in response to a second address signal (different from said first address signal), due to for example said first user being in/near Brussels and said second user being in/near Paris.

—Said time-dependency for example allows said first user after having entered a specific control signal (for example a mouse click on an icon for receiving the weather forecast) to receive first information from Monday till Friday (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and allows said first user after having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) to receive second information during the weekend (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example said first user working in Brussels and living in Antwerp.

—A second embodiment of the telecommunication system according to the invention is characterised in ~~that~~that said at least one part of said generator is located in said network.

—By locating said generator (substantially) in the network, the terminal just needs minimal adaptations or does not even need to be adapted at all.

—According to a first option, said generator corresponds with one or more Domain Name Servers or DNSs, with said location-dependencies being realisedrealized by storing in different DNSs different IP addresses but all to be read out in response to the same specific control signal. So, said first user being in/near Brussels and having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS in/near Brussels and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and a second user being in/near Paris and having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get a second IP address from a DNS in/near Paris and receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that at least parts of said DNS and generator are integrated.

—According to a second option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said

second option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

—According to a third option, said generator corresponds with one or more DNSs, with said time-dependencies being ~~realised~~realized by using clock signals for reading out from a DNS a first IP address in response to said specific control signal in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said specific control signal in case of said clock signal having a second value. So, said first user having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address from Monday till Friday, and said first user having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get a second IP address from a DNS and receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address) during the weekend, due to for example said first user working in Brussels and living in Antwerp. Said third option is very advantageous in that at least parts of said DNS and generator are integrated.

—According to a fourth option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in Antwerp. Said fourth option is very advantageous in that the DNS does not need to be adapted.



—A third embodiment of the system according to the invention is characterised in that said at least one part of said generator performs said generating in dependence of a location signal to be generated via said network.

—By providing said generator with said location signal originating from said Point-of-Presence or PoP (the telephone number of this PoP) or originating via said PoP (the user's telephone number or a user identification or the user's IP address), said generators (said DNSs in case of said first option as well as said converters in case of said second option) can be designed more generally and do not need to be adapted per location, due to said location signals taking care of the ~~individualisation~~. individualization.

—A fourth embodiment of the system according the invention is characterised in that at least one part of said generator is located in said terminal.

—By locating said generator (substantially) in the terminal, the network just needs minimal adaptations or does not even need to be adapted at all.

—According to a first option, said generator performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Thereto, said terminal for example receives location information from the network (in case of said terminal being a mobile terminal, base station controller or BSC information could be used, and in case of said terminal being a fixed or mobile terminal, PoP information could be used). Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for

example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

—According to a second option, said generator performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in

Antwerp. Said second option is very advantageous in that the DNS does not need to be adapted.

—A fifth embodiment of the system according the invention is characterised in that said at least one part of said generator performs said generating in dependence of a further location signal to be generated via said terminal.

—By providing said generator with said further location signal to be generated via said terminal, location-dependencies are introduced which are network-independently. For example, said further location signal originates from a Global Positioning System receiver or GPS receiver forming part of said terminal, or said further location signal is entered by said user, for example an area code. Then, in said terminal, in dependence of said further location signal, a specific control signal is converted into a location-dependent control signal, etc.

—The invention further relates to a network for use in a telecommunication system for receiving at least one control signal from a user via terminal and comprising said terminal and said network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

—The network according to the invention is characterised in that said network comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

—Embodiments of the network according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the network is involved.

—The invention yet further relates to a terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

—The terminal according to the invention is characterised in that said terminal comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

—Embodiments of the terminal according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the terminal is involved.

2006720 20564007

~~The invention also relates to a generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.~~

~~The generator~~The terminal according to the invention ~~is characterised in that said telecommunication system comprises said a~~ generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

~~Embodiments of the generator~~Embodiments of the terminal according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the ~~generator~~terminal is involved.

~~The invention yet also relates to a method~~generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The generator according to the invention generates at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the generator according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the generator is involved.

The invention yet also relates to a method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

~~—The method according to the invention is characterised in that said method comprises the step of generating at least one address signal in response to said at least one control signal in a user-dependent way.~~

~~—Embodiments of the method according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the method is involved.~~

US 6,055,542 discloses a system for displaying the content of a web page based on a user's interests, US 6,029,135 discloses a hypertext navigation system controlled by spoken words, US 5,764,639 as well as US 5,889,845 disclose a system for providing a remote user with a virtual presence to an office, US 6,052,725 discloses a non-local dynamic internet protocol addressing system, US 5,898,780 discloses an apparatus for authorizing remote internet access, and US 5,598,536 discloses an apparatus for providing remote users with the same unique IP address upon each network access. Neither one of these documents discloses the telecommunication system according to the invention. All references including further references cited with respect to and/or inside said references are considered to be incorporated in this patent application.

#### BRIEF DESCRIPTION OF THE DRAWING:

The invention will be further explained at the hand of an embodiment described with respect to a drawing, whereby

#### DETAILED DESCRIPTION OF THE INVENTION

Figure 1 discloses a telecommunication system according to the invention comprising a network according to the invention and a



terminal according to the invention and a generator according to the invention.

—The telecommunication system according to the invention as shown in figure 1 comprises a first, fixed terminal 1 according to the invention and a second, mobile (for example GSM or UMTS) terminal 2 according to the invention and a third, fixed terminal 6 according to the invention and a fourth, cordless (for example DECT) terminal 7 according to the invention and a network 3,4,5,90,91,92,93,94 according to the invention comprising a first switch 3, a second switch 4, a third switch 5, a Base Station Controller or BSC 90 (for example GSM or UMTS), a Base Station or BS 91 (for example GSM or UMTS), a Base Station or BS 92 (for example DECT), a generator 93 according to the invention and a memory 94.

—Terminal 1 (or 6) comprises a processor system 10 coupled via a control connection to man-machine-interface or ~~mmi~~MMI 11 (like a keyboard – display – microphone – loudspeaker – mouse – touchscreen etc.) and coupled via a bus 17 to transceiver 16 (comprising a modem function). Via said bus 17 as well as via control connections, processor system 10 is further coupled to receiving unit 13 and to transmitting unit 15. Via a bus 18, transceiver 16 is coupled to receiving unit 13 and to ~~mmi~~MMI 11. Via a bus 19, transceiver 16 is coupled to transmitting

unit 15 and to ~~mmi~~MMI 11. Processor system 10 is coupled to (and/or even comprises) a generator 12 and a memory 14, which both are coupled to ~~mmi~~MMI 11 via control connections.

—Terminal 2 (or 7) comprises a processor system 20 coupled via a control connection to man-machine-interface or ~~mmi~~MMI 21 (like a keyboard – display – microphone – loudspeaker – mouse – touchscreen etc.) and coupled via a bus 27 to transceiver 26 (comprising a modem function). Via said bus 27 as well as via control connections, processor system 20 is further coupled to receiving unit 23 and to transmitting unit 25. Via a bus 28, transceiver 26 is coupled to receiving unit 23 and to ~~mmi~~MMI 21. Via a bus 29, transceiver 26 is coupled to transmitting unit 25 and to ~~mmi~~MMI 21. Processor system 20 is coupled to (and/or even comprises) a generator 22 and a memory 24, which both are coupled to ~~mmi~~MMI 21 via control connections. Transceiver 26 is connected to an antennae.

—Switch 3 (or 5) comprises a processor system 30 coupled via a control connection to a coupling unit 31. Processor system 30 is coupled to (and/or even comprises) a generator 32 and a memory 34, which both are coupled to coupling unit 31 via control connections. Coupling unit 31 is further coupled to via control connections to a receiving unit 35 and a transmitting unit 36 and a processing unit 33.

——Switch 4 (or 5) comprises a processor system 40 coupled via a control connection to a coupling unit 41. Processor system 40 is coupled to (and/or even comprises) a generator 42 and a memory 44, which both are coupled to coupling unit 41 via control connections. Coupling unit 41 is further coupled to via control connections to a receiving unit 45 and a transmitting unit 46 and a processing unit 43.

——Transceiver 16 of terminal 1 is coupled via a connection 80 to coupling unit 31 of switch 3, which coupling unit 31 is further coupled via a connection 83 to coupling unit 41 of switch 4 and via a connection 81 to BSC 90, which is coupled via a connection 82 to BS 91 for mobile communication with terminal 2. Coupling unit 41 of switch 4 is further coupled via a connection 87 to generator 93 and via a connection 88 to memory 94 and via a connection 84 to switch 5, which via a connection 85 is coupled to terminal 6 and via a connection 86 is coupled to BS 92 for cordless communication with terminal 7.

——The telecommunication system according to the invention as shown in figure 1 functions as follows.

——According to a first embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has

been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via ~~mmi~~MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 2 via connection 81 and BSC 90 and connection 82 and BS 91. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather

**THE UNIVERSITY OF CHICAGO**

forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

—The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-weather-forecast-icon via mmiiicon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said

first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 7 via connection 86 and BS 92. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

——Of course, instead of one memory 94, several memories at different locations could be used.

——According to a first alternative to said first embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

——According to a second alternative to said first embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

——According to a second embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via ~~mmi~~MMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 under control of processor system 30. Generator 32 converts said URL into a first converted URL,



which via coupling unit 31 and connection 83 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

—The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-~~weather-forecast-icon via mmi~~icon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor

system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 under control of processor system 50. Generator 52 converts said URL into a second converted URL, which via coupling unit 51 and connection 84 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

——Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

—According to a first alternative to said second embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

—According to a second alternative to said second embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

—According to a third embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via ~~mmi~~MMI 21 for receiving the

local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 4 via BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83. In switch 4, said URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said URL into a first IP address (thereby using the fact that said URL has arrived via connection 83 and switch 3 in/near Brussels), which via coupling unit 41 under control of processor system 40 is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

—The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example

www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-weather-forecast-icon via mmiicon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 4 via BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84. In switch 4, said same URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said same URL into a second IP address (different from said first IP address, thereby using the fact that said URL has arrived via connection 84 and switch 5 in/near Paris), which via coupling unit 41 under control of processor system 40 is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being

100449507 024306

converted into different IP addresses in a location-dependent way, thereby using location signals generated via said network.

——Of course, instead of one memory 94, several memories at different locations could be used.

——According to a first alternative to said third embodiment, other location signals generated via said network are used, for example in case of terminal 2 being involved, location signals indicating that said URL has arrived via BS 91 and/or connection 82 and/or BSC 90 and/or connection 81 are supplied via connection 83 and coupling unit 41 to generator 42, and in case of terminal 7 being involved, location signals indicating that said URL has arrived via BS 92 and/or connection 86 are supplied via connection 84 and coupling unit 41 to generator 42. Or yet other location signals generated via said network are used, for example a telephone number of terminal 2 and/or 7, and/or an IP address of terminal 2 and/or 7, and/or a user identification number, in which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 44, for example.

—According to a second alternative to said third embodiment, further location signals generated via said terminal are used, for example in case of terminal 2 being involved, said terminal 2 could be provided with a Global Positioning System receiver or GPS receiver, whereby GPS information is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or said user enters an area code via ~~mmi~~MMI 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, and in case of terminal 7 being involved, said user could enter an area code via ~~mmi~~MMI 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

—According to a third alternative to said third embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

——According to a fourth alternative to said third embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

——According to a fourth embodiment, for example generator 93 is a Domain Name Server or DNS, and generators 22 and 72 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmiMMI 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) generating a Uniform Resource Locator or URL, which is supplied to generator 22 for converting said URL into a first converted URL (thereby in general generator 22 will use said location signals and/or said other location



signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in memory 24). Via transmitting unit 25 and/or transceiver 26, said first converted URL is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

—The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these

respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-weather-forecast-icon-via-mmiiicon via MMI 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) generating the same Uniform Resource Locator or URL, which is supplied to generator 72 for converting said URL into a second converted URL (thereby in general generator 72 will use said location signals and/or said other location signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in memory 74). Via transmitting unit 75 and/or transceiver 76, said second converted URL is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said

same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

——Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

——According to a first alternative to said fourth embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

——According to a second alternative to said fourth embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

——According to a fifth embodiment, a user using terminal 1 and being in/near Brussels has been connected to the INTERNET or an INTRANET via his terminal 1 and connection 80 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising

web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via ~~mmi~~MMI 11 for receiving the local weather forecast) which results in his browser (running in processor system 10) sending a Uniform Resource Locator or URL via transmitting unit 15 and/or transceiver 16 to switch 3 via connection 80. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 1 via connection 80. In terminal 1, said first IP address is received via transceiver 16 and/or receiving unit 13 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

—The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 6. At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 6 and connection 85 and coupling unit 51 of switch 5 and

connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via ~~mmi~~MMI 61 for receiving the local weather forecast) which results in his browser (running in processor system 60) sending the same Uniform Resource Locator or URL via transmitting unit 65 and/or transceiver 66 to switch 5 via connection 85. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 6 via connection 85. In terminal 6, said second IP address is received via transceiver 66 and/or receiving unit 63 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets

different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

——Of course, instead of one memory 94, several memories at different locations could be used.

——According to a first alternative to said fifth embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, etc. Or generators 12 and 62 are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

——According to a second alternative to said fifth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of terminal 1 and/or 6, and/or an IP address of terminal 1 and/or 6, and/or a user identification number (for example to be entered via mmiMMI 11 or 61 in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), in

10049507.021302

which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

—According to a third alternative to said fifth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via ~~mmi~~MMI 11 or 61, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

—According to a sixth embodiment, for example in addition to the location-dependencies described before, or completely separated from these location-dependencies described before, time-dependencies are introduced. Generator 93 corresponds with a DNS, with said time-dependencies being realised by using clock signals for reading out from said DNS a first IP address in response to said URL in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said URL in case of said clock signal having a second value. So, said user having entered said URL sometime from Monday till Friday (for example a mouse click on an icon for receiving

the weather forecast) will get said first IP address from said DNS and receive first information (weather forecast for Brussels) stored in said memory and read out from this memory in response to said first IP address, and said user having entered the same URL during the weekend (for example a mouse click on the same icon for receiving the weather forecast) will get said second IP address from said DNS and receive second information (weather forecast for Antwerp) stored in said memory and read out from said memory in response to said second IP address (different from said first IP address), due to for example said user working in Brussels and living in Antwerp.

—According to a first alternative to said sixth embodiment, generator 93 is a DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, with said DNS reading out a first IP address in response to said first converted URL and reading out a second IP address in response to said second converted URL etc. Said time-dependencies could again be ~~realised~~realized by using clock signals for reading out from said generators a first converted URL in response to said URL in case of a clock signal having a first value and for reading out from said generators a second converted URL in response to said URL in case of said clock signal having a second value. Or generators 12 and 62



are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

—According to a second alternative to said sixth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of a terminal, and/or an IP address of a terminal, and/or a user identification number (for example to be entered via an ~~mmi~~MMI in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), whereby said user for example could have informed said network before at which location he will be and/or what he would like to get/do etc.. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

—According to a third alternative to said sixth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via an ~~mmi~~MMI, which is supplied to a switch and for example stored in a memory in said switch, each time a

URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

——It should be noted that said location-dependency and said time-dependency are both just examples of user-dependencies, whereby the term "user-dependencies" is to be regarded to comprise any dependency related to a user, which is not limited to direct dependencies, but does also include indirect dependencies (like a first generator at a first location generating differently from a second generator at a second location), and may include user groups and user behaviour. Such dependencies can be adjusted by a user, and/or (pre)programmed, and/or dynamically adapted by the system in response to experiences from the past.

——The example of the weather forecast is just an example of a kind of information and does not exclude other kinds of information, like for example flight/train schedules, traffic jam overview, yellow pages, etc.. In general any kind of information in which a user is interested could be supplied to said user, whereby the invention defines, inter alia, how said user's behaviour adapts the part of said (kind of) information to be supplied to him.

10049507 024302

—All embodiments are just embodiments and do not exclude other embodiments not shown and/or described. All alternatives are just alternatives and do not exclude other alternatives not shown and/or described. Each (part of an) embodiment and/or each (part of an) alternative can be combined with any other (part of an) embodiment and/or any other (part of an) alternative. Terms like "in response to A" and "in dependence of B" do not exclude that there could be a further "in response to C" and a further "in dependence of D" etc.

—Each generator will generally comprise a memory (like for example a server) which is addressed in response to user-dependencies, whereby said user-dependent addressing could take place inside said generator as well as outside said generator. Thereto an addresser ~~addressor~~ could be used, which (like a hardware converter) converts an incoming address signal into an outgoing address signal for said memory, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. If not forming part of said generator, said addressor could for part of for example a switch. Such a generator could correspond with a DNS (or include a DNS or form part of a DNS).

—Each generator may alternatively be ~~realised~~ realized by a hardware converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals

004950 024303

like location signals etc. and/or clock signals etc. And/or said generator may be realised~~realised~~realized by a software converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. Therefore, said generator could be a computer program product for generating at least one address information-unit in response to at least one control information-unit in a user-dependent way (and for example running in one of said processor systems), and/or could (at least partly) be integrated with a browser, etc.

——For each one of said terminals and/or said switches, alternative hardware structures are available, like an integration of two or more separated parts into one new part, or the dividing of one part into at least two separated parts, or the placing of three or more parallel parts serially, or the placing of three or more serial parts parallelly, etc.

Claims

1. ~~1.~~ ~~\_\_\_\_\_~~ Telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said telecommunication system comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

comprises

a generator for ~~generating at least one address signal in response to said at least one control signal in a user-dependent way.~~

2. ~~2.~~ ~~\_\_\_\_\_~~ Telecommunication system according to claim 1, characterised ~~in that~~ said user-dependent way ~~comprises~~ comprising at least one location-dependency and/or at least one time-dependency.

3. ~~3.~~ ~~\_\_\_\_\_~~ Telecommunication system according to claim 1 ~~or 2~~, characterised ~~in that~~ 1. at least one part of said generator ~~is being~~ located in said network.

4. ~~4.~~ Telecommunication system according to claim 3, ~~characterised in that~~ said at least one part of said generator ~~performs~~performing said generating in dependence of a location signal to be generated via said network.
5. ~~5.~~ Telecommunication system according to claim ~~1 or 2~~, ~~characterised in that~~1, at least one part of said generator ~~is~~being located in said terminal.
6. ~~6.~~ Telecommunication system according to claim ~~3, 4 or 5~~, ~~characterised in that~~ said at least one part of said generator ~~performs~~performing said generating in dependence of a further location signal to be generated via said terminal.
7. ~~7.~~ Network for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and said network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, ~~characterised in that~~ said network ~~comprises~~comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.



8. Terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said terminal comprising a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

9. Generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, said telecommunication system comprising said generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

~~8. Terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least~~

~~one address signal, characterised in that said terminal comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.~~

~~9. Generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said telecommunication system comprises said generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.~~

2. ~~10. Method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be~~Method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to~~supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said method comprises~~be supplied to said

1004507 054001

terminal and stored at at least one memory location defined by at  
least one address signal, said method comprising the step of  
generating at least one address signal in response to said at least  
one control signal in a user-dependent way.

2025-07-01 10:04:50Z 034302

way.

2025-07-20 10:54:00

### Abstract

——Known telecommunication systems comprising an internet terminal and a network for providing internet access/service offer a limited number of user-possibilities, which can be increased by introducing user-dependencies into the conversion of a (part of a) Uniform Resource Locator or URL into an IP address. This IP address ~~defines~~ defines

the information to be supplied to said terminal, now user-dependently, for example location-dependently and/or time-dependently. Thereto, location information (Domain Name Server or DNS with location dependent content, Point-of-Presence or PoP information, terminal's IP address, terminal's phone number, user-identification, Global Positioning System or GPS information, base station controller or BSC information, area codes entered by said user) originating from said network or from said terminal and/or timing information usually originating from said network are used.

Sole figure

i/p rts

-1-

DescriptionTelecommunication System, and Network, and Terminal, and Generator,  
and Method

The invention relates to a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

Such a telecommunication system is known in general, with said terminal for example being a fixed analog or digital terminal comprising an analog or digital modem (such a combination for example being an analog or digital screenphone or a pc) or being a mobile (for example GSM or UMTS) or a cordless (for example DECT) terminal, with each one of said terminals nowadays usually being provided with a browser, and with said control signal for example being a (part of a) Uniform Resource Locator or URL (and/or with said control signal being converted into said (part of a) URL) to be entered by said user for example through text via a terminal's keyboard or through a mouse click via a terminal's mouse or through a touch via a terminal's touch screen or through voice/speech via a terminal's microphone. At least a part of said network corresponds with at least a part of an INTERNET and/or INTRANET, and comprises said memory (for example a server) in which said information is stored at said at least one memory location defined by said at least one address signal (which address signal for example corresponds with an IP address

10/049507, 021302

or for example is generated in response to said IP address), which information is to be supplied to said terminal in response to said control signal. Thereto, a Domain Name Server or DNS (usually located in said network) is used to convert said (part of a) URL into said IP address, which IP address is sent back to said (browser in said) terminal. In response to the receival of this IP address, said browser establishes for example a TCP (Transmission Control Protocol) or a UDP (User Datagram Protocol) connection with for example a (part of a) server as defined by said IP address for receiving said information.

Such a telecommunication system is disadvantageous, inter alia, due to being user-friendly insufficiently.

It is an object of the invention, inter alia, to provide a telecommunication system as described in the preamble, which is more user-friendly.

Thereto, the telecommunication system according to the invention is characterised in that said telecommunication system comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

By introducing said generator for generating in a user-dependent way, the telecommunication system has been individualised. As a consequence, a first user entering a specific control signal will receive first information stored in a first memory and read out from this first memory in response to a first address signal, and a second user entering the same specific control signal will receive second information (different from said first information) stored in said first or a second memory and read out from said first or second memory in response to a second address

10049507 "021300

signal (different from said first address signal), due to for example a user identification (comprising for example the terminal's IP address and/or a number of a so-called source port) being involved in a conversion of said (part of a) URL into said IP address.

The invention is based on the insight, inter alia, that an individualised telecommunication system based upon at least one user-dependency is more user-friendly.

The invention solves the problem, inter alia, of providing a telecommunication system which is more user-friendly.

A first embodiment of the telecommunication system according to the invention is characterised in that said user-dependent way comprises at least one location-dependency and/or at least one time-dependency.

By introducing said location-dependency, a first user being in/near Brussels and entering a specific control signal (for example a mouse click on an icon for receiving the weather forecast) will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and a second user being in/near Paris and entering the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example said first user being in/near Brussels and said second user being in/near Paris.

Said time-dependency for example allows said first user after having entered a specific control signal (for example a mouse click on

40049507 "024303



an icon for receiving the weather forecast) to receive first information from Monday till Friday (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to a first address signal, and allows said first user after having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) to receive second information during the weekend (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to a second address signal (different from said first address signal), due to for example said first user working in Brussels and living in Antwerp.

A second embodiment of the telecommunication system according to the invention is characterised in that at least one part of said generator is located in said network.

By locating said generator (substantially) in the network, the terminal just needs minimal adaptations or does not even need to be adapted at all.

According to a first option, said generator corresponds with one or more Domain Name Servers or DNSs, with said location-dependencies being realised by storing in different DNSs different IP addresses but all to be read out in response to the same specific control signal. So, said first user being in/near Brussels and having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS in/near Brussels and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and a second user being in/near Paris and having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get

a second IP address from a DNS in/near Paris and receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that at least parts of said DNS and generator are integrated.

According to a second option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said

10049507 "034303

second option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

According to a third option, said generator corresponds with one or more DNSs, with said time-dependencies being realised by using clock signals for reading out from a DNS a first IP address in response to said specific control signal in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said specific control signal in case of said clock signal having a second value. So, said first user having entered said specific control signal (for example a mouse click on an icon for receiving the weather forecast) will get a first IP address from a DNS and receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address from Monday till Friday, and said first user having entered the same specific control signal (for example a mouse click on the same icon for receiving the weather forecast) will get a second IP address from a DNS and receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address) during the weekend, due to for example said first user working in Brussels and living in Antwerp. Said third option is very advantageous in that at least parts of said DNS and generator are integrated.

According to a fourth option, said generator is located in said network between terminal (for example near a Point-of-Presence or PoP) and DNS, and performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted into

a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in Antwerp. Said fourth option is very advantageous in that the DNS does not need to be adapted.

A third embodiment of the system according to the invention is characterised in that said at least one part of said generator performs said generating in dependence of a location signal to be generated via said network.

By providing said generator with said location signal originating from said Point-of-Presence or PoP (the telephone number of this PoP) or originating via said PoP (the user's telephone number or a user identification or the user's IP address), said generators (said DNSs in case of said first option as well as said converters in case of said second option) can be designed more generally and do not need to be adapted per location, due to said location signals taking care of the individualisation.

A fourth embodiment of the system according the invention is characterised in that at least one part of said generator is located in said terminal.

By locating said generator (substantially) in the terminal, the network just needs minimal adaptations or does not even need to be adapted at all.

According to a first option, said generator performs a kind of a conversion by converting at different locations said specific control signal into a location-dependent control signal which is different per location. Thereto, said terminal for example receives location information from the network (in case of said terminal being a mobile terminal, base station controller or BSC information could be used, and in case of said terminal being a fixed or mobile terminal, PoP information could be used). Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first location-dependent control signal in response to which a DNS in/near Brussels will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said second user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second location-dependent control signal (different from said first location-dependent control signal) in response to which a DNS in/near Paris will generate said second IP address and said second user will receive second information (weather forecast for Paris) stored in said first or a second memory and read out from said first or second memory in response to

said second IP address (different from said first IP address), due to for example said first user being in/near Brussels and said second user being in/near Paris. Said first option is very advantageous in that the (content of a) DNS does not need to be adapted per location.

According to a second option, said generator performs a kind of a conversion by converting said specific control signal into a time-dependent control signal. Then, said specific control signal as entered by said first user (for example a mouse click on an icon for receiving the weather forecast) will be converted in said terminal into a first time-dependent control signal from Monday till Friday in response to which a DNS will generate said first IP address and said first user will receive first information (weather forecast for Brussels) stored in a first memory and read out from this first memory in response to said first IP address, and the same specific control signal as entered by said first user (for example a mouse click on the same icon for receiving the weather forecast) will be converted in said terminal into a second time-dependent control signal (different from said first time-dependent control signal) during the weekend in response to which a DNS will generate said second IP address and said first user will receive second information (weather forecast for Antwerp) stored in said first or a second memory and read out from said first or second memory in response to said second IP address (different from said first IP address), due to for example said first user working in Brussels and living in Antwerp. Said second option is very advantageous in that the DNS does not need to be adapted.

A fifth embodiment of the system according the invention is characterised in that said at least one part of said generator performs

said generating in dependence of a further location signal to be generated via said terminal.

By providing said generator with said further location signal to be generated via said terminal, location-dependencies are introduced which are network-independently. For example, said further location signal originates from a Global Positioning System receiver or GPS receiver forming part of said terminal, or said further location signal is entered by said user, for example an area code. Then, in said terminal, in dependence of said further location signal, a specific control signal is converted into a location-dependent control signal, etc.

The invention further relates to a network for use in a telecommunication system for receiving at least one control signal from a user via terminal and comprising said terminal and said network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The network according to the invention is characterised in that said network comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the network according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the network is involved.

The invention yet further relates to a terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory

20250720 05:40:07

comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The terminal according to the invention is characterised in that said terminal comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the terminal according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the terminal is involved.

The invention also relates to a generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

The generator according to the invention is characterised in that said telecommunication system comprises said generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the generator according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the generator is involved.

The invention yet also relates to a method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal.

10049507 031306



The method according to the invention is characterised in that said method comprises the step of generating at least one address signal in response to said at least one control signal in a user-dependent way.

Embodiments of the method according to the invention correspond with embodiments of the telecommunication system according to the invention as far as the method is involved.

US 6,055,542 discloses a system for displaying the content of a web page based on a user's interests, US 6,029,135 discloses a hypertext navigation system controlled by spoken words, US 5,764,639 as well as US 5,889,845 disclose a system for providing a remote user with a virtual presence to an office, US 6,052,725 discloses a non-local dynamic internet protocol addressing system, US 5,898,780 discloses an apparatus for authorizing remote internet access, and US 5,598,536 discloses an apparatus for providing remote users with the same unique IP address upon each network access. Neither one of these documents discloses the telecommunication system according to the invention. All references including further references cited with respect to and/or inside said references are considered to be incorporated in this patent application.

The invention will be further explained at the hand of an embodiment described with respect to a drawing, whereby

figure 1 discloses a telecommunication system according to the invention comprising a network according to the invention and a terminal according to the invention and a generator according to the invention.

The telecommunication system according to the invention as shown in figure 1 comprises a first, fixed terminal 1 according to the invention and a second, mobile (for example GSM or UMTS) terminal 2 according to the invention and a third, fixed terminal 6 according to the invention and a fourth, cordless (for example DECT) terminal 7 according to the invention and a network 3,4,5,90,91,92,93,94 according to the invention comprising a first switch 3, a second switch 4, a third switch 5, a Base Station Controller or BSC 90 (for example GSM or UMTS), a Base Station or BS 91 (for example GSM or UMTS), a Base Station or BS 92 (for example DECT), a generator 93 according to the invention and a memory 94.

Terminal 1 (or 6) comprises a processor system 10 coupled via a control connection to man-machine-interface or mmi 11 (like a keyboard - display - microphone - loudspeaker - mouse - touchscreen etc.) and coupled via a bus 17 to transceiver 16 (comprising a modem function). Via said bus 17 as well as via control connections, processor system 10 is further coupled to receiving unit 13 and to transmitting unit 15. Via a bus 18, transceiver 16 is coupled to receiving unit 13 and to mmi 11. Via a bus 19, transceiver 16 is coupled to transmitting unit 15 and to mmi 11. Processor system 10 is coupled to (and/or even comprises) a generator 12 and a memory 14, which both are coupled to mmi 11 via control connections.

Terminal 2 (or 7) comprises a processor system 20 coupled via a control connection to man-machine-interface or mmi 21 (like a keyboard - display - microphone - loudspeaker - mouse - touchscreen etc.) and coupled via a bus 27 to transceiver 26 (comprising a modem function). Via said bus 27 as well as via control connections, processor system 20 is further coupled to receiving unit 23 and to transmitting

unit 25. Via a bus 28, transceiver 26 is coupled to receiving unit 23 and to mmi 21. Via a bus 29, transceiver 26 is coupled to transmitting unit 25 and to mmi 21. Processor system 20 is coupled to (and/or even comprises) a generator 22 and a memory 24, which both are coupled to mmi 21 via control connections. Transceiver 26 is connected to an antennae.

Switch 3 (or 5) comprises a processor system 30 coupled via a control connection to a coupling unit 31. Processor system 30 is coupled to (and/or even comprises) a generator 32 and a memory 34, which both are coupled to coupling unit 31 via control connections. Coupling unit 31 is further coupled to via control connections to a receiving unit 35 and a transmitting unit 36 and a processing unit 33.

Switch 4 (or 5) comprises a processor system 40 coupled via a control connection to a coupling unit 41. Processor system 40 is coupled to (and/or even comprises) a generator 42 and a memory 44, which both are coupled to coupling unit 41 via control connections. Coupling unit 41 is further coupled to via control connections to a receiving unit 45 and a transmitting unit 46 and a processing unit 43.

Transceiver 16 of terminal 1 is coupled via a connection 80 to coupling unit 31 of switch 3, which coupling unit 31 is further coupled via a connection 83 to coupling unit 41 of switch 4 and via a connection 81 to BSC 90, which is coupled via a connection 82 to BS 91 for mobile communication with terminal 2. Coupling unit 41 of switch 4 is further coupled via a connection 87 to generator 93 and via a connection 88 to memory 94 and via a connection 84 to switch 5, which via a connection 85 is coupled to terminal 6 and via a connection 86 is coupled to BS 92 for cordless communication with terminal 7.

The telecommunication system according to the invention as shown in figure 1 functions as follows.

According to a first embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmi 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 2 via connection 81 and BSC 90 and connection 82 and BS 91. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

20051229 095400

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via mmi 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 7 via connection 86 and BS 92. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets

10049507 03400

different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said first embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said first embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a second embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmi 21 for receiving the local weather forecast) which results in his browser

(running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 3 via BS 91 and connection 82 and BSC 90 and connection 81. In switch 3, said URL is sent via coupling unit 31 to generator 32 under control of processor system 30. Generator 32 converts said URL into a first converted URL, which via coupling unit 31 and connection 83 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via mmi 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76

10049507-094309

to switch 5 via BS 92 and connection 86. In switch 5, said same URL is sent via coupling unit 51 to generator 52 under control of processor system 50. Generator 52 converts said URL into a second converted URL, which via coupling unit 51 and connection 84 and coupling unit 41 of switch 4 and connection 87 is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said second embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said second embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.



According to a third embodiment, a user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmi 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) sending a Uniform Resource Locator or URL via transmitting unit 25 and/or transceiver 26 to switch 4 via BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83. In switch 4, said URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said URL into a first IP address (thereby using the fact that said URL has arrived via connection 83 and switch 3 in/near Brussels), which via coupling unit 41 under control of processor system 40 is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via mmi 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) sending the same Uniform Resource Locator or URL via transmitting unit 75 and/or transceiver 76 to switch 4 via BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84. In switch 4, said same URL is sent via coupling unit 41 to generator 42 (being for example a Domain Name Server or DNS) under control of processor system 40. Generator 42 converts said same URL into a second IP address (different from said first IP address, thereby using the fact that said URL has arrived via connection 84 and switch 5 in/near Paris), which via coupling unit 41 under control of processor system 40 is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at

2025-09-20 10:49:50 -054306

different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way, thereby using location signals generated via said network.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said third embodiment, other location signals generated via said network are used, for example in case of terminal 2 being involved, location signals indicating that said URL has arrived via BS 91 and/or connection 82 and/or BSC 90 and/or connection 81 are supplied via connection 83 and coupling unit 41 to generator 42, and in case of terminal 7 being involved, location signals indicating that said URL has arrived via BS 92 and/or connection 86 are supplied via connection 84 and coupling unit 41 to generator 42. Or yet other location signals generated via said network are used, for example a telephone number of terminal 2 and/or 7, and/or an IP address of terminal 2 and/or 7, and/or a user identification number, in which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 44, for example.

According to a second alternative to said third embodiment, further location signals generated via said terminal are used, for example in case of terminal 2 being involved, said terminal 2 could be provided with a Global Positioning System receiver or GPS receiver, whereby GPS information is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start

10049507 "034303"

of an INTERNET and/or INTRANET session, or said user enters an area code via mmi 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, and in case of terminal 7 being involved, said user could enter an area code via mmi 21, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

According to a third alternative to said third embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a fourth alternative to said third embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a fourth embodiment, for example generator 93 is a Domain Name Server or DNS, and generators 22 and 72 respectively just convert the same URL into a first converted URL and a second converted URL respectively. A user using terminal 2 and being in/near Brussels (so BS 91 being located in/near Brussels) has been connected to the INTERNET or an INTRANET via his terminal 2 and BS 91 and connection 82 and BSC 90 and connection 81 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [aww.alcatel.com](http://aww.alcatel.com), which web-sites are

stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmi 21 for receiving the local weather forecast) which results in his browser (running in processor system 20) generating a Uniform Resource Locator or URL, which is supplied to generator 22 for converting said URL into a first converted URL (thereby in general generator 22 will use said location signals and/or said other location signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in memory 24). Via transmitting unit 25 and/or transceiver 26, said first converted URL is sent to DNS 93. DNS 93 converts said first converted URL into a first IP address, which is sent back to terminal 2. In terminal 2, said first IP address is received via transceiver 26 and/or receiving unit 23 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 7 (so BS 92 being located in/near Paris). At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 7 and BS 92 and connection 86 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for

example a server comprising web-sites like for example www.alcatel.com and/or aww.alcatel.com, which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via mmi 71 for receiving the local weather forecast) which results in his browser (running in processor system 70) generating the same Uniform Resource Locator or URL, which is supplied to generator 72 for converting said URL into a second converted URL (thereby in general generator 72 will use said location signals and/or said other location signals and/or said yet other location signals and/or said further location signals as described before, which for example are exchanged each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc. and/or which for example could be stored in memory 74). Via transmitting unit 75 and/or transceiver 76, said second converted URL is sent to DNS 93. DNS 93 converts said second converted URL into a second IP address (different from said first IP address), which is sent back to terminal 7. In terminal 7, said second IP address is received via transceiver 76 and/or receiving unit 73 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different URLs in a location-dependent way, which result in different IP addresses, etc.

Of course, instead of one DNS 93, several DNSs at different locations could be used. And instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said fourth embodiment, BS 92 is capable of communicating with terminal 2, for example either due to BS 92 being a DECT base station and terminal 2 being designed to also communicate according to DECT or due to terminal 2 being a GSM and/or UMTS terminal and BS 92 being designed to (also) communicate according to GSM and/or UMTS, in which case said user may carry his terminal 2 with him from Brussels to Paris, etc.

According to a second alternative to said fourth embodiment, said first user uses terminal 2, and a second user uses terminal 7, etc.

According to a fifth embodiment, a user using terminal 1 and being in/near Brussels has been connected to the INTERNET or an INTRANET via his terminal 1 and connection 80 and coupling unit 31 of switch 3 and connection 83 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Brussels. Thereto, he enters a specific control signal (for example a mouse click on a weather-forecast-icon via mmi 11 for receiving the local weather forecast) which results in his browser (running in processor system 10) sending a Uniform Resource Locator or URL via transmitting unit 15 and/or transceiver 16 to switch 3 via connection 80. In switch 3, said URL is sent via coupling unit 31 to generator 32 (being for example a Domain Name Server or DNS located in/near Brussels) under control of processor

system 30. Generator 32 converts said URL into a first IP address, which via coupling unit 31 under control of processor system 30 is sent back to terminal 1 via connection 80. In terminal 1, said first IP address is received via transceiver 16 and/or receiving unit 13 and supplied to said browser, which in response connects memory 94 for receiving first information (weather forecast for Brussels) stored at said first IP address or at an other address being related to said first IP address.

The next day, said user travels to Paris to visit his mother company, and during his visit he gets terminal 6. At a moment, said user has been connected to the INTERNET or an INTRANET via his terminal 6 and connection 85 and coupling unit 51 of switch 5 and connection 84 and coupling unit 41 of switch 4 and connection 88, with memory 94 being for example a server comprising web-sites like for example [www.alcatel.com](http://www.alcatel.com) and/or [www.alcatel.com](http://www.alcatel.com), which web-sites are stored at the respective IP addresses or at other addresses related to these respective IP addresses. Then said user wants to check for example the weather forecast for Paris. Thereto, he enters the same specific control signal (for example a mouse click on the same weather-forecast-icon via mmi 61 for receiving the local weather forecast) which results in his browser (running in processor system 60) sending the same Uniform Resource Locator or URL via transmitting unit 65 and/or transceiver 66 to switch 5 via connection 85. In switch 5, said same URL is sent via coupling unit 51 to generator 52 (being for example a Domain Name Server or DNS located in/near Paris) under control of processor system 50. Generator 52 converts said same URL into a second IP address (different from said first IP address), which via coupling unit 51 under control of processor system 50 is sent back to terminal 6 via connection 85. In terminal 6, said second IP address is

10049507.05406



received via transceiver 66 and/or receiving unit 63 and supplied to said browser, which in response connects memory 94 for receiving second information (weather forecast for Paris) stored at said second IP address or at an other address being related to said second IP address. So, said user, although generating the same URL at different locations, gets different information per location, due to said same URL being converted into different IP addresses in a location-dependent way.

Of course, instead of one memory 94, several memories at different locations could be used.

According to a first alternative to said fifth embodiment, generator 93 is a Domain Name Server or DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, etc. Or generators 12 and 62 are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

According to a second alternative to said fifth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of terminal 1 and/or 6, and/or an IP address of terminal 1 and/or 6, and/or a user identification number (for example to be entered via mmi 11 or 61 in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), in which cases said user for example should have informed said network before at which location he will be. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by

20061229 100449507 021300

sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

According to a third alternative to said fifth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via mmi 11 or 61, which is supplied to switch 4 and for example stored in memory 44, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

According to a sixth embodiment, for example in addition to the location-dependencies described before, or completely separated from these location-dependencies described before, time-dependencies are introduced. Generator 93 corresponds with a DNS, with said time-dependencies being realised by using clock signals for reading out from said DNS a first IP address in response to said URL in case of a clock signal having a first value and for reading out from said DNS a second IP address in response to said URL in case of said clock signal having a second value. So, said user having entered said URL sometime from Monday till Friday (for example a mouse click on an icon for receiving the weather forecast) will get said first IP address from said DNS and receive first information (weather forecast for Brussels) stored in said memory and read out from this memory in response to said first IP address, and said user having entered the same URL during the weekend (for example a mouse click on the same icon for receiving the weather forecast) will get said second IP address from said DNS and receive second information (weather forecast for Antwerp) stored in said memory and read out from said memory in response to said second IP address (different from said first IP address), due to for example said user working in Brussels and living in Antwerp.

40049507 "034303

According to a first alternative to said sixth embodiment, generator 93 is a DNS, and generators 32 and 52 respectively just convert the same URL into a first converted URL and a second converted URL respectively, with said DNS reading out a first IP address in response to said first converted URL and reading out a second IP address in response to said second converted URL etc. Said time-dependencies could again be realised by using clock signals for reading out from said generators a first converted URL in response to said URL in case of a clock signal having a first value and for reading out from said generators a second converted URL in response to said URL in case of said clock signal having a second value. Or generators 12 and 62 are used for said converting, with generator 93 being a DNS and/or with generators 32 and 42 and 52 being DNSs, etc.

According to a second alternative to said sixth embodiment, location signals generated via said network are used, for example said location signals and/or said other location signals indicating that said URL has arrived via connection 80 or 81 or via connection 85 or 86 or via connection 83 or 84 etc., and/or said yet other location signals generated via said network are used, for example a telephone number of a terminal, and/or an IP address of a terminal, and/or a user identification number (for example to be entered via an mmi in the form of a code and/or password or by using a smart card + card reader or by using speech or a finger print, etc.), whereby said user for example could have informed said network before at which location he will be and/or what he would like to get/do etc.. This could be done for example via said INTERNET and/or INTRANET, or via special telephone calls, or by sending emails etc., with such information being stored in memory 34 and/or 44 and/or 54 for example.

According to a third alternative to said sixth embodiment, further location signals generated via said terminal are used, for example said user could enter an area code via an mmi, which is supplied to a switch and for example stored in a memory in said switch, each time a URL is generated or just once after the start of an INTERNET and/or INTRANET session, or via special telephone calls, or by sending emails etc.

It should be noted that said location-dependency and said time-dependency are both just examples of user-dependencies, whereby the term "user-dependencies" is to be regarded to comprise any dependency related to a user, which is not limited to direct dependencies, but does also include indirect dependencies (like a first generator at a first location generating differently from a second generator at a second location), and may include user groups and user behaviour. Such dependencies can be adjusted by a user, and/or (pre)programmed, and/or dynamically adapted by the system in response to experiences from the past.

The example of the weather forecast is just an example of a kind of information and does not exclude other kinds of information, like for example flight/train schedules, traffic jam overview, yellow pages, etc.. In general any kind of information in which a user is interested could be supplied to said user, whereby the invention defines, inter alia, how said user's behaviour adapts the part of said (kind of) information to be supplied to him.

All embodiments are just embodiments and do not exclude other embodiments not shown and/or described. All alternatives are just alternatives and do not exclude other alternatives not shown and/or described. Each (part of an) embodiment and/or each (part of an) alternative can be combined with any other (part of an) embodiment

and/or any other (part of an) alternative. Terms like "in response to A" and "in dependence of B" do not exclude that there could be a further "in response to C" and a further "in dependence of D" etc.

Each generator will generally comprise a memory (like for example a server) which is addressed in response to user-dependencies, whereby said user-dependent addressing could take place inside said generator as well as outside said generator. Thereto an addressor could be used, which (like a hardware converter) converts an incoming address signal into an outgoing address signal for said memory, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. If not forming part of said generator, said addressor could for part of for example a switch. Such a generator could correspond with a DNS (or include a DNS or form part of a DNS).

Each generator may alternatively be realised by a hardware converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. And/or said generator may be realised by a software converter, which converts an incoming address signal into an outgoing address signal for said DNS, possibly in dependence of certain signals like location signals etc. and/or clock signals etc. Therefore, said generator could be a computer program product for generating at least one address information-unit in response to at least one control information-unit in a user-dependent way (and for example running in one of said processor systems), and/or could (at least partly) be integrated with a browser, etc.

For each one of said terminals and/or said switches, alternative hardware structures are available, like an integration of two or more separated parts into one new part, or the dividing of one part into at

least two separated parts, or the placing of three or more parallel parts serially, or the placing of three or more serial parts parallelly, etc.

2025 FEB 20 10:49:50 AM

### Claims

1. Telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said telecommunication system comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.
2. Telecommunication system according to claim 1, characterised in that said user-dependent way comprises at least one location-dependency and/or at least one time-dependency.
3. Telecommunication system according to claim 1 or 2, characterised in that at least one part of said generator is located in said network.
4. Telecommunication system according to claim 3, characterised in that said at least one part of said generator performs said generating in dependence of a location signal to be generated via said network.
5. Telecommunication system according to claim 1 or 2, characterised in that at least one part of said generator is located in said terminal.

20250720 10554007

6. Telecommunication system according to claim 3, 4 or 5, characterised in that said at least one part of said generator performs said generating in dependence of a further location signal to be generated via said terminal.

7. Network for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and said network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said network comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

8. Terminal for use in a telecommunication system for receiving at least one control signal from a user via said terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said terminal comprises a generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

9. Generator for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least



one address signal, characterised in that said telecommunication system comprises said generator for generating at least one address signal in response to said at least one control signal in a user-dependent way.

10. Method for use in a telecommunication system for receiving at least one control signal from a user via a terminal and comprising said terminal and a network for in response to said at least one control signal addressing a memory comprising information to be supplied to said terminal and stored at at least one memory location defined by at least one address signal, characterised in that said method comprises the step of generating at least one address signal in response to said at least one control signal in a user-dependent way.

### Abstract

Known telecommunication systems comprising an internet terminal and a network for providing internet access/service offer a limited number of user-possibilities, which can be increased by introducing user-dependencies into the conversion of a (part of a) Uniform Resource Locator or URL into an IP address. This IP address defines the information to be supplied to said terminal, now user-dependently, for example location-dependently and/or time-dependently. Thereto, location information (Domain Name Server or DNS with location dependent content, Point-of-Presence or PoP information, terminal's IP address, terminal's phone number, user-identification, Global Positioning System or GPS information, base station controller or BSC information, area codes entered by said user) originating from said network or from said terminal and/or timing information usually originating from said network are used.

Sole figure

Fig. 1



**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that my residence, mailing address and citizenship are as stated below next to my name: that I verily believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought in the application entitled:

"TELECOMMUNICATION SYSTEM, AND NETWORK, AND TERMINAL, AND GENERATOR, AND METHOD",  
which application is:

☐ the attached application  
(for original application)

☐ Application No. \_\_\_\_\_  
(Confirmation No. \_\_\_\_\_) filed  
\_\_\_\_\_, and amended on \_\_\_\_\_

(for declaration not accompanying application)

that I have reviewed and understand the contents of the specification of the above-identified application, including the claims, as amended by any amendment referred to above; that I acknowledge my duty to disclose information of which I am aware and which is material to the patentability of this application as defined in 37 C.F.R. 1.56, that I hereby claim priority benefits under Title 35, United States Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, §119(e) of any United States provisional application(s), or §365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate or of any PCT International application having a filing date before that of the application on which priority is claimed:

Application Number	Country	Filing Date	Priority Claimed	
			Yes	No
00 440 174.1	Europe	June 14, 2000	<input checked="" type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under 35 United States Code §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in a listed prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge my duty to disclose any information material to the patentability of this application as defined in 37 C.F.R. 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application No.

Filing Date

Status

34  
I hereby appoint John H. Mion, Reg. No. 18,879; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Brian W. Hannon, Reg. No. 32,778; Abraham J. Rosner, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102; Brett S. Sylvester, Reg. No. 32,765; Robert M. Masters, Reg. No. 35,603; George F. Lehnigk, Reg. No. 36,359; John T. Callahan, Reg. No. 32,607; Steven M. Gruskin, Reg. No. 36,818; Peter A. McKenna, Reg. No. 38,551 and Edward F. Kenehan, Reg. No. 28,962, my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and request that all correspondence about the application be addressed to **SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC, 2100 Pennsylvania Avenue, N.W., Washington, D.C. 20037-3213.**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Date Feb. 4, 2002 1-00 First Inventor Marco PETERS  
First Name Middle Initial Last Name

Residence Bergen op Zoom Netherlands MLX Signature Marco Peters  
City State/Country

Mailing Address: Zwartewaal 39  
4617 NS Bergen op Zoom, Netherlands

Citizenship Netherlands

2-00  
Date Feb. 4, 2002

Second Inventor Suresh

LEROY

First Name

Middle Initial

Last Name

Residence Vlimmeren  
City

Belgium

State/Country

BEX

Signature

Suresh Leroy

Mailing Address:

Bloemenstraat 18

2340 Vlimmeren, Belgium

Citizenship Belgian

Date Third Inventor

First Name

Middle Initial

Last Name

Residence

City

State/Country

Signature

Mailing Address:

Citizenship

Date Fourth Inventor

First Name

Middle Initial

Last Name

Residence

City

State/Country

Signature

Mailing Address:

Citizenship

Date Fifth Inventor

First Name

Middle Initial

Last Name

Residence

City

State/Country

Signature

Mailing Address:

Citizenship

Date Sixth Inventor

First Name

Middle Initial

Last Name

Residence

City

State/Country

Signature

Mailing Address:

Citizenship